



STONE LOOK

AFFINITY™

GLAZED PORCELAIN FLOOR, GLAZED CERAMIC  
WALL & MOSAIC



 daltile®  
IMAGINE WHAT'S POSSIBLE™



# AFFINITY™

GLAZED PORCELAIN FLOOR, GLAZED CERAMIC  
WALL & MOSAIC

## Modern Take on a Classic Stone Look

Feature the soft, natural look of contemporary stone in your home with Affinity™. A warm neutral color palette contributes to this product's authentic and stylish look. Affinity eases the design process, offering floor, wall, mosaic and trim tile.

### • NATURAL ATTRIBUTES

- Subtle movement and features reminiscent of limestone contribute to its authentic natural stone look
- Warm, neutral color palette

### • STYLISH Demeanor

- Ideal complement to contemporary designs and modern décor
- Coordinating wall, floor, mosaic and trim add finishing design touches

### STONE LOOK

### USAGE



FLOOR



WALL



COUNTERTOP



SHOWER  
FLOOR



EXTERIOR  
FLOOR



STEPWISE™



TRU-EDGE™



MADE IN  
THE U.S.A.



LARGE  
FORMAT



MOSAIC/  
DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



PGI

LOW HIGH

### SPECIAL FEATURES

NOT APPLICABLE  
FOR ALL PRODUCTS  
IN THIS SERIES. SEE  
CHARTS FOR FULL  
PRODUCT DETAILS.

Above and cover photos feature Affinity™ Cream 12 x 24 floor tile on the floor with Cream 10 x 14 wall tile and 2 x 2 mosaic on the wall.



# STONE LOOK

# AFFINITY™

GLAZED PORCELAIN FLOOR, GLAZED CERAMIC WALL & MOSAIC

### SIZES:



FINISHES: MATTE

### COLOR PALETTE



CREAM



BEIGE



GRAY

### GLAZED PORCELAIN FLOOR TILE



CREAM AF01



BEIGE AF02



GRAY AF03

### GLAZED CERAMIC WALL TILE



CREAM AF01



BEIGE AF02



GRAY AF03

### 2 x 2 GLAZED CERAMIC MOSAIC



CREAM AF01



BEIGE AF02



GRAY AF03



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



CLIMATEPRO™



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT [WWW.DAL TILE.COM](http://WWW.DAL TILE.COM) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

# AFFINITY™

GLAZED PORCELAIN FLOOR, GLAZED CERAMIC WALL & MOSAIC

STONE LOOK

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	18 x 18 Floor Tile	(17-3/4" x 17-3/4") (45.20 cm x 45.20 cm)	5/16"	17.60	8
	12 x 24 Floor Tile	(11-13/16" x 23-13/16") (30.00 cm x 60.48 cm)	5/16"	15.60	8
	12 x 12 Floor Tile	(11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	5/16"	14.55	15
	10 x 14* Wall Tile	(9-13/16" x 13-15/16") (24.99 cm x 35.40 cm)	5/16"	14.25	15
	2 x 2 Mosaic* (Dot-mounted)	(12" x 24" Sheet) (30.48 cm x 60.96 cm Sheet)	1/4"	24.00	12

\* Glazed Ceramic

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓†
Wet & Level – Interior Floor	≥ 0.42	✓†
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓†
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).

### APPLICATION NOTES:

Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Wall and mosaic tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

† Floor and mosaic tile only.

\* Mosaic tile only.

 **POST-CONSUMER RECYCLED MATERIALS**

 **PRE-CONSUMER RECYCLED MATERIALS**

 **MADE IN THE U.S.A.**




 **REVEAL IMAGING®**

All or select items within this series meet the requirements for these qualifications. For more information, visit [daltile.com](http://daltile.com).

**ZEROTOX**  
Healthy Homes | Healthy Planet

**CERTIFIED PORCELAIN**  
TILE  
0.5% or less water absorption

## TRIM

	Type	Number	Size	Pieces/ Carton
	Bullnose	P-43C9	3 x 12	30
	Wall Bullnose*	S-4310 (10" side)	3 x 10	54
	Wall Bullnose Corner*	SN-4310	3 x 3	32

\* Glazed Ceramic

## INSTALLATION

### Grout Joint Recommendation

### Shade Variation

**Floor:** 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern. When multiple sizes are installed in a modular pattern, please specify same size caliber at time of order.)



**Wall:** 1/16"

**Mosaic:** 1/8"

## PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 0.5%	< 20.0%	< 3.0%
Breaking Strength	C648	> 275 lbs	120-230 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	4.0-6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: [daltile.com/information/TestResults](http://daltile.com/information/TestResults).

## DURABILITY

### Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	④	All Residential / Commercial

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [daltile.com/Factors](http://daltile.com/Factors).

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [daltile.com/LargeTiles](http://daltile.com/LargeTiles) for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit [daltile.com](http://daltile.com).

7834 C.F. Hawn Freeway,  
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of  
Daltile® products and information,  
visit our website at [daltile.com](http://daltile.com).

 **daltile**  
IMAGINE WHAT'S POSSIBLE™

©2021 Daltile (5/21)