WALL

AMITY™

GLASS WALL & MOSAIC

daltile®
IMAGINE WHAT'S POSSIBLE™

AMITY™

GLASS WALL & MOSAIC

Elevate With Inviting Accents

Come home to effortless design with the sleek glass wall tile and mosaic collection, Amity™. Offered in two modern shapes, Amity is a clean-lined choice for backsplashes and decorative accents. While giving a nod to a vintage aesthetic, Amity brings a contemporary update to your home with monochromatic colors in an inviting neutral palette.

- DÉCOR OPPORTUNITY
  - Featured in five monochromatic colors
  - Available in a 3 x 6 glass wall tile and a glass random linear mosaic

- MODERN UPDATES
  - Crafted from smooth, sheen glass
  - A neutral backdrop for surrounding décor

Cover photo features Uptown Glass™ Posh Chiffon on the wall.
Above photo features Uptown Glass™ Frost Moka 1" hexagon mosaic on the wall.

SIZES:

3 x 6
Wall Tile

2 x 2 Random
Linear Mosaic

FINISHES: GLOSSY

## COLOR PALETTE

| WHITE | TAUPE | BEIGE | GREY | BROWN |

## 3 x 6 4MM GLASS WALL TILE*

| WHITE AM50 | TAUPE AM51 | BEIGE AM53 | GREY AM52 | BROWN AM54 |

* 3 x 6 wall tile sold individually
  by the piece.

## 4MM RANDOM LINEAR MOSAIC

| WHITE AM50 | TAUPE AM51 | BEIGE AM53 | GREY AM52 | BROWN AM54 |

WATERPROOF   STAINPROOF   DENTPROOF   SCRATCH-RESISTANT¹
*Applicable to products with Matte and Textured Finishes   FIRE-RESISTANT¹
*Not Applicable to Mesh-Mounted Mosaics   INDOOR/OUTDOOR   SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DALTILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	3 x 6 Wall Tile	(2-7/8" x 5-13/16") (7.28 cm x 14.75 cm)	3/16"	6.00	50
	Random Linear Mosaic (Mesh-mounted)	(11-7/16" x 13-7/8") (29.03 cm x 35.23 cm)	3/16"	13.95	15

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✔
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Wall tile and mosaic suitable for interior applications only.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" Approximately	Low (V1)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 100 lbs
Scratch Hardness	MOHS	4.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

NOTES

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.2 standards.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Use of a latex modified thin-set is recommended for installation.