

# **MOSAICS**

COLOR WHEEL™ COLLECTION - GLAZED CERAMIC

# A Spectacular Spectrum

The element of color is visually represented in Color Wheel™. This vibrant collection offers a wide spectrum of colorful selections from bright and pigmented hues to neutral and earthy tones. A favorite of artists and designers, Color Wheel provides the perfect palette to inspire the imagination.

#### COLOR SCHEME

- Eight rich semi-gloss colorful accents
- Plus, eight coordinating neutral tones in semi-gloss and matte finishes

#### ARTISTIC INSPIRATIONS

- Stylish shapes from unique linear sizes to exciting mosaic designs

### MOSAIC





































### SIZES:



2 x 2 Mosaic





1 - 1/2" Hexagon Mosaic



 $1 \times 3$ Herringbone Mosaic



1 x 3 Lattice Weave Mosaic

FINISHES: MATTE | GLOSSY

#### SEMI-GLOSS



**BLACK** K111 (2)



ARCTIC WHITE 0190 (1)



**BISCUIT** K175 (1)



**URBAN PUTTY** 0161 (2)



GRAY 0109 (2)



ARCHITECTURAL DESERT GRAY X114 (1)



SUEDE GRAY 0182 (2)



CHALKBOARD 0180 (2)

#### **MATTE**



MATTE BLACK K711 (2)



MATTE ARCTIC WHITE 0790 (1)



MATTE BISCUIT K775 (1)



MATTE URBAN PUTTY 0761 (2)



MATTE ARCHITECTURAL GRAY X714 (1) GRAY 0709 (2)



MATTE DESERT



MATTE SUEDE GRAY 0782 (2)



MATTE CHALKBOARD 0780 (2)

## ACCENT+



MUSTARD 1012 (3)



ORANGE BURST CURRANT 1097 (3)



SH17 (3)



**EMERALD** 0115 (3)



SEA BREEZE 1174 (3)



OCEAN BLUE 1049 (3)




NAVY K189 (3)



PLUM CRAZY 1178 (3)

### SIZES




1 x 3 HERRINGBONE MOSAIC (DOT-MOUNTED ON 9" x 12" SHEET)




1.5" HEXAGON MOSAIC (DOT-MOUNTED ON 12" x 11" SHEET)



1 x 3 I ATTICE WEAVE MOSAIC (DOT-MOUNTED ON 12 x 12 SHEET)



2 x 2 MOSAIC (DOT-MOUNTED ON 12" x 24" SHEET)



1.5" ARCTIC WHITE WITH BLACK HEXAGON MOSAIC\* CW50 GLOSS AND CW51 MATTE (MESH-MOUNTED ON 14" x 12" SHEET)

(1), (2) and (3) indicate price groups. (1) being the least expensive.

Shapes stocked in all colors. Blends and patterns are also available on a made to order basis. \* Stocked in Arctic White with Black (both CW50 gloss and CW51 matte).

Other pattern and blend options available (in any size, color or finish) on a made to order basis.

+ Accent available in Semi-Gloss finish only.







DENTPROOF









## **MOSAICS**

## COLOR WHEEL™ COLLECTION - GLAZED CERAMIC

#### SIZES

|   |  | Thickness      | Sq. Ft./<br>Carton | Pieces/<br>Carton |
|---|--|----------------|--------------------|-------------------|
| 2 x 2 Mosaic<br>(Dot-mounted)   | (12" x 24" Sheet)<br>(30.48 cm x 60.96 cm<br>Sheet)      | 1/4"<br>(6 mm) | 24.00              | 12                |
| 1.5" Hexagon<br>Mosaic<br>(Dot-mounted<br>on 12" x 11" Sheet)                           | (11-5/8" x 10-1/4" Sheet)<br>(28.89 cm x 26.04 cm Sheet) | 1/4"<br>(6 mm) | 9.72               | 12                |
| 1.5" Arctic White<br>& Black Hexagon<br>Mosaic*<br>(Mesh-mounted<br>on 14" x 12" Sheet) | (14" x 11-1/2" Sheet)<br>(35.56 cm x 29.21 cm Sheet)     | 1/4"<br>(6 mm) | 10.00              | 10                |
| 1 x 3<br>Herringbone<br>Mosaic<br>(Dot-mounted)   | (9" x 12" Sheet)<br>(22.86 cm x 30.48 cm Sheet)          | 1/4"<br>(6 mm) | 6.00               | 10                |
| 1 x 3 Lattice<br>Weave Mosaic<br>(Dot-mounted)  | (12" x 12" Sheet)<br>(30.48 cm x 30.48 cm Sheet)         | 1/4"<br>(6 mm) | 10.00              | 10                |

<sup>\*</sup> Stocked in Arctic White with Black (both CW50 gloss and CW51 matte). Other pattern and blend options available (in any size, color or finish) on a made to order basis.

### LRV & MUNSELL

| Color #    | LRV<br>Illuminate-OBS: F02-02 (CWF) | Munsell        |
|------------|-------------------------------------|----------------|
| SEMI-GLOSS |                                     |                |
| 0190       | 83.9                                | 7.0Y 9.2/0.2   |
| K175       | 75.9                                | 5.2Y 8.8/0.9   |
| 0161       | 48.0                                | 1.7Y 7.3/1.5   |
| 0109       | 37.9                                | 6.0Y 6.6/1.0   |
| X114       | 43.7                                | 1.4GY 7.0/0.3  |
| 0182       | 22.6                                | 1.9B 5.3/0.1   |
| 0180       | 11.4                                | 1.3B 3.9/0.4   |
| K111       | 5.0                                 | 10.0B 2.6/0.1  |
| MATTE      |                                     |                |
| 0790       | 83.4                                | 4.9Y 9.2/0.2   |
| K775       | 75.9                                | 5.2Y 8.8/0.9   |
| 0761       | 48.1                                | 2.5Y 7.3/1.5   |
| 0709       | 36.9                                | 5.6Y 6.5/1.0   |
| X714       | 43.9                                | 3.6GY 7.0/0.4  |
| 0782       | 22.3                                | 9.8G 5.3/0.1   |
| 0780       | 11.1                                | 0.6B 3.9/0.4   |
| K711       | 5.8                                 | 3.3PB 2.8/0.1  |
| ACCENT     |                                     |                |
| K189       | 5.9                                 | 5.0PB 2.9/1.2  |
| 1012       | 48.1                                | 9.7YR 7.2/6.9  |
| 1049       | 18.0                                | 1.9B 5.0/4.5   |
| 1097       | 26.4                                | 10.1R 5.6/10.2 |
| 0115       | 12.4                                | 3.4G 4.2/4.6   |
| 1174       | 9.1                                 | 5.8PB 3.6/5.6  |
| 1178       | 6.8                                 | 5.9RP 3.1/2.0  |
| SH17       | 14.0                                | 5.1R 4.4/11.1  |

#### TRIM

| Туре      | Number   | Size           | Pieces/<br>Carton |
|-----------|----------|----------------|-------------------|
| 12" Jolly | S-1/212J | 1/2 x 11-15/16 | 12                |

Jolly suitable for wall applications only.

#### INSTALLATION

| Grout Joint Recommendation | Shade Variation |  |
|----------------------------|-----------------|--|
| Mosaic: 1/8"               | Low (V1)        |  |

## PERFORMANCE CHARACTERISTICS

|                     | ASTM# | Gloss<br>Result | Matte<br>Result |
|---------------------|-------|-----------------|-----------------|
| Water Absorption    | C373  | < 3.0%          | < 3.0%          |
| Breaking Strength   | C648  | > 250 lbs       | > 250 lbs       |
| Scratch Hardness    | MOHS  | 4.0-6.0         | 8.0             |
| Chemical Resistance | C650  | Resistant       | Resistant       |

For additional information on test results, visit us at: daltile.com/information/TestResults.

#### NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

## **MOSAICS**

### COLOR WHEEL™ COLLECTION - GLAZED CERAMIC

#### **APPLICATIONS**

|  | Target<br>DCOF wet | Suitable    |
|--|--------------------|-------------|
| Dry & Level – Interior Floor   | N/A                | <b>/</b> *  |
| Wet & Level – Interior Floor   | ≥ 0.42             | <b>/</b> *  |
| Shower Floors (Residential or Light Commercial)  | ≥ 0.42             | <b>/</b> *  |
| Exterior Floor Applications<br>(including patios, pool decking & other<br>wet areas with minimal footwear) | ≥ 0.60             |             |
| Ramps & Inclines   | ≥ 0.65             |             |
| Walls/Backsplashes   | N/A                | <b>~</b>    |
| Countertops  | N/A                | <b>√</b> ∗† |
| Pool Linings   | N/A                | <b>~</b>    |

A DCOF value of  $\geq$ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest $^{"}$ , visit daltile.com/DCOF.

#### APPLICATION NOTES:

Mosaics suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

- \* Matte Mosaics Only
- <sup>†</sup> Darker colors may show scratches

#### **DURABILITY**

| Floor Surface Wear Resistance |                       |   |                                    |  |
|-------------------------------|-----------------------|---|------------------------------------|--|
| 1                             | Residential Bathrooms | 3 | All Residential / Light Commercial |  |
| 2                             | All Residential Areas | 4 | All Residential / Commercial       |  |

Note: Matte colors only.









To view the complete collection of Daltile® products and information, visit our website at daltile.com.

