WALL

# WALL COMPOSITION<sup>™</sup> GLAZED CERAMIC



## WALL COMPOSITION<sup>™</sup> GLAZED CERAMIC

## Created for a Dramatic Finish

Make your room a work of art with Composition tile. Its matte and glossy neutral colors attract architects, designers, builders and homeowners alike. Use the large 12 x 24 size to create grand statements and impressive accent walls. With its crisp graphic and Tru-Edge formatting, Composition is the ideal wall tile for creating dramatic spaces.

- STYLISH CONFIGURATION
  - Features Tru-Edge™ to create a sleek, seamless look
  - Neutral color palette complements an array of styles
- PERFECT FINISH
  - Available in two finishes for stylized look
  - Finish the look with coordinating trim





<u></u>\_\_\_\_\_\_

SEE CHARTS FOR FULL PRODUCT DETAILS

atures Gesso Matte 12 x 24 wall tile. eatures Visionary Gloss 12 x 24 wall tile.

## WALL COMPOSITION<sup>™</sup> GLAZED CERAMIC

SIZES:	
12 x 24 Floor Tile	10 x 14 Floor Tile
FINISHES: M	IATTE   GLOSSY












WALL TILE





VISIONARY GLOSS CP05





CANVAS GLOSS CP03 / CANVAS MATTE CP04

### JOLLY TRIM

VISIONARY GLOSS CP05

CANVAS GLOSS CP03 / CANVAS MATTE CP04

PROVIDENTIAL GLOSS CP06

GESSO GLOSS CP01 / GESSO MATTE CP02

GESSO GLOSS CP01 / GESSO MATTE CP02





SCRATCH-RESISTANT'

FIRE-RESISTANT



NT<sup>™</sup> SIMPLICLEAN<sup>™</sup>

VISIT THE WHY TILE PAGE AT WWW.DALTILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

## WALL COMPOSITION<sup>™</sup> GLAZED CERAMIC

SIZES				
		Thickness	Sq. Ft./ Carton	Pieces/ Carton
	(12" x 24") (30.00 cm x 60.00 cm)	3/8" 9.30mm	15.52	8
	(9-5/8" x 13-3/4") (24.42 cm x 34.83 cm)	5/16" 7.90mm	13.65	15

\* Available in CP01, CP03, CP05 and CP06 only

#### APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	$\checkmark$
Countertops	N/A	
Pool Linings	N/A	

#### APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

#### TRIM

	Туре	Number	Size	Pieces/ Carton
	12" Jolly	S-1/212J	1/2 x 12	12
INSTAL	LATION			
Grout Jo	int Recommend	lation	Shade Var	iation
staggere	/8" (1/8" when ir d brick-joint pator ot exceed 33%)	9	Low (	√1)
<b>10 x 14:</b> 1,	/8"		High (	V3)

#### PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20.5%
Breaking Strength	C648	120 - 230lbs
Scratch Hardness	MOHS	4.0-6.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

#### NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.





REVEAL IMAGING®

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.

7834 C.F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.

