



WOOD LOOK

FLOOR | WALL

EMBLEM™  
GLAZED CERAMIC

 daltile®  
IMAGINE WHAT'S POSSIBLE™

FLOOR | WALL

**EMBLEM™**

GLAZED CERAMIC

## Classic Richness and Warmth of Natural Wood with Rugged Durability

The classic look of rustic wood gives this tile a warm, inviting appearance with the richness found in nature. Now, with Emblem™ from Daltile, you can achieve the elegance of hardwood without compromise. Emblem mimics the look of natural wood, but in a ceramic tile that provides both beauty and outstanding durability.

- **REVEAL IMAGING®**
  - This proprietary imaging technology provides a realistic wood look, complete with knots and grain for an exact, elegant style
- **EASY INSTALLATION & MAINTENANCE**
  - Ceramic tile offers a more durable material for high traffic areas, with an ease of maintenance
- **EXCELLENT VALUE**
  - Get the natural look you desire at a price point that fits your budget

**WOOD  
LOOK**

USAGE



SEE CHARTS FOR FULL  
PRODUCT DETAILS

SPECIAL FEATURES

Above and cover photos feature Brown 7 x 20 field tile in a staggered brick-joint pattern on the floor.

SIZES:



FINISHES: MATTE

COLOR PALETTE



BEIGE



GRAY



BROWN

GLAZED CERAMIC FLOOR with REVEAL IMAGING®



BEIGE EM01



GRAY EM03



BROWN EM04



SLIP RESISTANT



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT™  
\*Applicable to products with Matte and Textured Finishes




FIRE-RESISTANT™  
\*Not Applicable to Mesh-Mounted Mosaics



SIMPLICLEAN™

## SIZES

	Thickness	Sq. Ft./ Carton	Pieces/ Carton
 7 x 20 Floor Tile	5/16"	10.89	11
		(7-1/16" x 19-11/16") (18.00 cm x 50.00 cm)	

This product is manufactured regionally. Slight variances in size and shading may occur between regions. Please contact your sales representative to verify carton square footage. As with all tile projects, be sure to purchase sufficient quantities with your initial order.

## APPLICATIONS


	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).

### APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

## TRIM

Type	Number	Size	Pieces/ Carton
 Bullnose	S-435K9	3-1/2 x 20	10

## INSTALLATION

### Grout Joint Recommendation

### Shade Variation

3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)



## PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 7.0%
Breaking Strength	C648	> 250 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: [daltile.com/information/TestResults](http://daltile.com/information/TestResults).

## DURABILITY

### Floor Surface Wear Resistance

1 Residential Bathrooms (3)	All Residential / Light Commercial
2 All Residential Areas	4 All Residential / Commercial

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [daltile.com/Factors](http://daltile.com/Factors).

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [daltile.com/LargeTiles](http://daltile.com/LargeTiles) for more information.



All or select items within this series meet the requirements for these qualifications. For more information, visit [daltile.com](http://daltile.com).