



MOSAIC

WALL

IDYLIC BLENDS™

GLASS, STONE & LVT MOSAIC



 daltile®
IMAGINE WHAT'S POSSIBLE™

WALL

IDYLLIC BLENDS™

GLASS, STONE & LVT MOSAIC

The Striking Look of Cubism

Be inspired by the intriguing geometric shapes of Idyllic Blends™. Influenced by cubic art, linear and hexagonal mosaics are pieced together randomly for a visually captivating appearance. Idyllic Blends was designed to stand out, making it perfect for walls and backsplashes. The collection playfully brings together cool undertones and warm shades.

- **OUTSTANDING DESIGN**
 - Captivating stone and wood visuals
 - Unique combination of cool and warm shades
- **ARTISTIC APPROACH**
 - Color and gradient variation for an unexpected, exciting design
 - Random linear and 2-inch hexagon mosaics
 - Available in four mixed-shade color blends

MOSAIC

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



SEE CHARTS FOR FULL PRODUCT DETAILS

SPECIAL FEATURES

Cover and above photos feature Idyllic Blends™ Tranquil Snow 2" hexagon mosaic on the backsplash.

2" HEXAGON MOSAIC



TRANQUIL SNOW IB01



SERENE STORM IB04



SYLVAN SUNSET IB02



RUSTIC EVE IB03

SIZES:



2" Hexagon Mosaic



Random Linear Mosaic

FINISHES: SATIN | GLOSSY

RANDOM LINEAR MOSAIC



TRANQUIL SNOW IB01



SERENE STORM IB04



SYLVAN SUNSET IB02



RUSTIC EVE IB03



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT*
*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT*
*Not Applicable to Mesh-Mounted Mosaics



CLIMATEPRO™





SIMPLICLEAN™

IDYLLIC BLENDS™

GLASS, STONE & LVT MOSAIC

MOSAIC

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	2" Hexagon Mosaic (Mesh-mounted)	(10-7/8" x 11-1/16" Sheet) (27.60 cm x 28.09 cm Sheet)	3/16"	11.40	15
	Random Linear Mosaic (Mesh-mounted)	(13-7/8" x 11-9/16" Sheet) (35.22 cm x 71.34 cm Sheet)	3/16"	14.40	15

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" Approximately	 Random (V4)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 100 lbs
Scratch Hardness	MOHS	4.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltille.com/information/TestResults.

NOTES

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A1372 standards.

For additional information refer to "Factors to Consider" at daltille.com/Factors.

 PRE-CONSUMER
RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information, visit daltille.com.