



CONCRETE LOOK

INDUSTRIAL PARK™

COLORBODY™ PORCELAIN WITH STEPWISE™ TECHNOLOGY

INDUSTRIAL PARK™

COLORBODY™ PORCELAIN WITH STEPWISE™ TECHNOLOGY

A Modern Mix of Style, Functional Design and Technical Performance

Inspired by terrazzo and concrete, Industrial Park™ asserts itself with solid colors punctuated by randomly placed colored flakes of varying dimension for optimal visual appeal. Industrial Park™ is one of Daltile's growing list of series to feature StepWise™ technology. This patent-pending process combines superior slip resistance with exceptional cleanability making Industrial Park a great choice for commercial applications including ramps. StepWise™ technology and beauty converge delivering solid design and useful function to any space.

- COMMERCIAL SOPHISTICATION
 - Concrete look with flakes for a fresh new commercial style
 - Modular sizes and complementary colors enhance design options
- STEPWISE™ TECHNOLOGY
 - Provides a superior slip resistance in commercial and mixed used applications
 - Exceptional cleanability for easy maintenance when compared to other slip resistance surfaces

CONCRETE LOOK

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



PC



LOW HIGH

SPECIAL FEATURES

SEE CHARTS FOR FULL PRODUCT DETAILS

Above and cover photos feature Industrial Park™ Light Gray 24 x 24 and Charcoal Gray 24 x 24 on the floor.

CONCRETE LOOK

INDUSTRIAL PARK™

COLORBODY™ PORCELAIN
WITH STEPWISE™ TECHNOLOGY

SIZES:



24 x 24
Floor Tile



12 x 24
Floor Tile



12 x 12
Floor Tile

FINISHES: MATTE

COLOR PALETTE



LIGHT
GRAY



NATURAL
BEIGE



CHARCOAL
GRAY



LIGHT GRAY IP07



NATURAL BEIGE IP06



CHARCOAL GRAY IP09

50% MORE
SLIP RESISTANT
THAN ORDINARY TILE*

*When compared to tile meeting ANSI standards.



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT*



FIRE-RESISTANT*



INDOOR/OUTDOOR



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

INDUSTRIAL PARK™

COLORBODY™ PORCELAIN WITH STEPWISE™ TECHNOLOGY

CONCRETE LOOK



ALL STYLE. NO SLIPS.

Don't tip-toe through life. Step stylishly on non-slip tile that's 50% more slip resistant than ordinary tile. And because it's Daltile, you'll find beautiful natural looks that are waterproof, scratchproof, stainproof and dentproof.

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 24 Floor Tile	(23-13/16" x 23-13/16") (60.48 cm x 60.48 cm)	5/16"	15.76	4
	12 x 24 Floor Tile	(11-7/8" x 23-5/8") (30.23 cm x 60.12 cm)	5/16"	17.60	9
	12 x 12 Floor Tile	(11-7/8" x 11-7/8") (30.23 cm x 30.23 cm)	5/16"	14.55	15

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	✓
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.



LEARN MORE

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



IMAGINE WHAT'S POSSIBLE™

©2022 Daltile (8/22)

TRIM

	Type	Number	Size	Pieces/ Carton
	Bullnose	P-43C9	3 x 12	30
	Cove Base	P-36C9TB	6 x 12	22
	Cove Base Outcorner	PC-36C9TB	6 x 1	15

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

Cove base and cove corner trim are suitable for non-freezing climates only.

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/16"	High (V3)

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3	All Residential / Light Commercial
2 All Residential Areas	④	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.