

2.0 mm | 12 Mil  
**CYROSE™**  
GLUE DOWN

**PROSERIES™**  
LUXURY VINYL FLOORING  
daltile®

6 x 48 WOOD LOOK PLANKS



WHITE ASH CY30



COASTAL GREY CY31



BARNWOOD CY34



HONEY MAPLE CY32



EARLY AMERICAN CY33



2.0 mm | 12 Mil  
**CYROSE™**  
GLUE DOWN



### DESIGN & SIZE

Product Type:	Glue Down LVF
Thickness:	2.0 mm
Wear Layer:	12 Mil (0.3048 mm)
Finish:	Polyurethane protective coating
Size (nominal):	6" W x 48" L Plank
Size (actual):	152.4 mm x 1,219.2 mm
Packaging:	54 sq. ft. per carton   27 pieces per carton
Weight:	1.35 lbs per piece   37.7 lbs per carton
Installation & Adhesive:	Glue down and install using ProSeries by Daltile Adhesive; see <a href="http://daltile.com/LVF">daltile.com/LVF</a> for more recommended installation and adhesive information

### SERVICE

Warranty:	Limited 6 Year Light Commercial Limited 15 Year Residential
-----------	--

### PERFORMANCE & CHARACTERISTICS

Construction:	Light Commercial Grade Luxury Vinyl Flooring; 100% Virgin
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2421 - Passes - $\pm 0.010$ " max
Size and Tolerance:	ASTM F2421 - Passes - $\pm 0.016$ in. / linear foot
Thickness:	ASTM F386 - Passes - as specified $\pm 0.005$ in
Flexibility:	ASTM F137 - Passes - 1" mandrel
Dimensional Stability:	ASTM F2199 - Passes - 0.020 in. / linear foot max
Static Load Limit:	ASTM F970 - Passes, modified at 1000 psi
Coefficient of Friction (Slip Resistance)	ASTM D2047 - Passes - $\geq 0.80$ (Dry)
Residual Indentation:	ASTM F1914 - Passes - Average less than 8% maximum single reading 10%
Resistance To Chemicals:	ASTM F925 - Passes - No more than a slight change
Resistance To Light:	ASTM F1515 - Passes - $\Delta E \leq 8$
Resistance To Heat:	ASTM F1514 - Passes - $\Delta E \leq 8$
Critical Radiant Flux:	ASTM E648 - Passes - Class 1 ( $> 0.45$ W/cm <sup>2</sup> )
Smoke Density:	ASTM E662 Part A - Passes - $< 450$



7834 C.F. Hawn Freeway,  
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at [daltile.com/LVF](http://daltile.com/LVF)



©2020 Dal-Tile Corporation (09/20)