



CONCRETE LOOK

SCRAPBOOK™  
GLAZED PORCELAIN



 daltile®  
IMAGINE WHAT'S POSSIBLE™

# SCRAPBOOK™

GLAZED PORCELAIN

Scrapbook™ tells a romantic story that beautifully weaves the old and new to create an instant heirloom effect. Discover how the vintage-inspired decorative 8" hexagon and the 2 x 8 floor tile in perfectly muted colors can seamlessly combine or stand alone in your pattern choice. Scrapbook captures heritage appreciation in the modern world.

## CONCRETE LOOK

### USAGE



### SPECIAL FEATURES

Cover photo features Scrapbook™ Petal 8" hexagon decorative accent matte on the wall and Emerson Wood™ Butter Pecan 6 x 48 matte on the floor.

Above photo features Scrapbook™ Memory Grey, Keepsake Blue and Album White 8" hexagon matte on the floor and Keepsake Blue 2 x 8 matte on the far wall.

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES:



2 x 8  
Floor Tile



8" Hexagon  
Floor Tile



FINISHES: MATTE

2 x 8 FLOOR TILE



ALBUM WHITE SB30



CHERISHED GREIGE SB33



MEMORY GREY SB32



KEEPSAKE BLUE SB34

8" HEXAGON FLOOR TILE



ALBUM WHITE SB30



CHERISHED GREIGE SB33




MEMORY GREY SB32



KEEPSAKE BLUE SB34


8" HEXAGON DECORATIVE ACCENT




PETAL SB35



QUILT SB36



MEMORY GREY  
ASANOHA SB38



KEEPSAKE BLUE  
ASAHOHA SB39



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



CLIMATEPRO™



SIMPLICLEAN™

# SCRAPBOOK™

GLAZED PORCELAIN

CONCRETE LOOK

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	2 x 8 Floor Tile	(2" x 7-15/16") (5.08 mm x 20.26 mm)	3/8"	4.68	36
	8" Hexagon Floor Tile	(7-7/8" x 9-1/8") (20.04 cm x 23.16 cm)	5/16"	9.37	25
	8" Hexagon Decorative Accent	(7-7/8" x 9-1/8") (20.04 cm x 23.16 cm)	5/16"	9.37	25

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).

### APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
3/16"	 High (V3)

## PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: [daltile.com/information/TestResults](http://daltile.com/information/TestResults).

## DURABILITY

### Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	④	All Residential / Commercial

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [daltile.com/Factors](http://daltile.com/Factors).

Use of a latex modified thin-set is recommended for installation. For more information, visit [daltile.com](http://daltile.com).



All or select items within this series meet the requirements for these qualifications. For more information, visit [daltile.com](http://daltile.com).



LEARN MORE

7834 C.F. Hawn Freeway,  
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at [daltile.com](http://daltile.com).



IMAGINE WHAT'S POSSIBLE™

©2022 Daltile (5/22)