

UPTOWN GLASS™

GLASS MOSAICS

Create a Statement with Eye Catching Prints and Striking Finishes

With contemporary urban inspiration, this chic collection reflects the most current design trends. Featuring a range of beautiful solid colors as well as metallic elements sprinkled into marble visuals, Uptown Glass" mosaics allow easy style expression for accent walls, backsplashes and floors. Also, with the addition of new technology, many of the patterns and finishes in this collection are made to withstand pool and spa chemicals, providing an excellent choice to make a splash with pool or hot tub designs.

- FASHION FORWARD
 - Exotic prints, geometric patterns and beautiful iridescent tones make a bold and unique statement in any space
- ECO FRIENDLY
 - Contains 98% recycled content
- PERFECT FOR MANY SPACES
 - Excellent choice for accent walls and backsplashes
 - Many styles are suitable for pool use allowing for an impressive decorative accent





USAGE


































OT APPLICABLE
OR ALL PRODUCT

UPTOWN GLASS™ GLASS MOSAICS

| SIZES:





1" Hexagon Mosaic (Mesh-mounted)

FINISHES: MATTE | GLOSSY

1 x 1 METRO MOSAICS







METRO CREAM UP07

METRO TAUPE UP09

METRO GRAY UP08

1" HEXAGON MOSAIC







POSH CHIFFON UP27



POSH BUBBLY UP28



POSH BRONZE UP29




POSH SPRITZER UP24*



POSH SPARKLER UP26*



MATTE ALABASTER UP20*



MATTE FROST MOKA UP21*



MATTE EBONY UP22*



CARRARA UP23*



ALABASTER UP17



FROST MOKA UP18



EBONY UP19

* Suitable for floor use.











CLIMATEPRO"



SIMPLICLEAN™

UPTOWN GLASS™

GLASS MOSAICS

SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
	(12-1/4" x 12-1/4" Sheet) (31.00 cm x 31.00 cm Sheet)	4.4 mm	21.00	20
	(11-3/4" x 11-1/2" Sheet) (30.00 cm x 29.00 cm Sheet)	4.4 mm	16.92	18

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	√ *
Wet & Level – Interior Floor	≥ 0.42	√ *
Shower Floors (Residential or Light Commercial)	≥ 0.42	√ *
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	√ **

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods

Uptown Glass 1 x 1 Metro series contains Molten Glass. Molten glass characteristics include irregular edges and some variation in size. These characteristics are inherent in standard production. These subtle size and shape variations impact the final grout joint appearance and enhance the natural visual of this series.

* 1" Hexagon mosaic UP20, UP21, UP22, UP23, UP24, UP25 and UP26 only.

INSTALLATION

Grout Joint Recommendation	Shade Variation		
Mosaic: 1/8"	Random (V4)		

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor / 1" Hexagon Result (UP20-UP26)	Metro & Wall / Hexagon Result (UP07, UP08, UP09, UP17, UP18, UP19, UP27, UP28, UP29)
Water Absorption	C373	< 0.5%	< 0.5%
Breaking Strength	C648	> 250 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	4.0
Chemical Resistance	C650	Resistant	Resistant
Abrasion Resistance	C1027	N/A	N/A

For additional information on test results, visit us at: daltile.com/information/TestResults.

NOTES

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.2 standards.

Use of a white latex modified thin-set is recommended for installation.



All or select items within this series meet the requirements for these qualifications. For more product information, visit daltile.com.





LEARN MORE

^{**} UP27, UP28, UP29 not suitable for pool linings.