



WOOD LOOK

FLOOR | WALL

WILLOW BEND™

GLAZED PORCELAIN

 daltile®
IMAGINE WHAT'S POSSIBLE™

FLOOR | WALL

WILLOW BEND™

GLAZED PORCELAIN

Delightful Style With Dramatic Size

Make your space more inviting with the delightful design of Willow Bend. Using Reveal Imaging® to create crisp and stunning graphics, this wood look porcelain tile inspires serenity. Offered in a 6 x 24 plank and featuring an even larger 6 x 36 size, Willow Bend embraces both traditional and modern style.

• IN-DEMAND COLORS AND SIZE

- Two versatile plank sizes: 6 x 24 and an even larger 6 x 36 plank
- Popular wood colors including white, smoky brown and dark brown
- Reveal Imaging® Technology creates crisp and stunning graphics

• DURABLE DESIGN

- Ease of maintenance and durability perfect for high traffic areas
- Designed for both residential and commercial settings

WOOD
LOOK

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER
FLOOR



EXTERIOR
FLOOR



STEPWISE™



TRU-EDGE™



MADE IN
THE U.S.A.



LARGE
FORMAT



MOSAIC/
DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



SEE CHARTS FOR FULL
PRODUCT DETAILS

SPECIAL FEATURES

Above and cover photos feature Willow Bend™ Dark Brown 6 x 24 on the floor.

SIZES:



6 x 36
Floor Tile



6 x 24
Floor Tile

FINISHES: MATTE

FLOOR TILE



WHITE WB01



DARK BROWN WB03



SMOKY BROWN WB02



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT™
*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT™
*Not Applicable to Mesh-Mounted Mosaics



CLIMATEPRO™





SIMPLICLEAN™

WILLOW BEND™

GLAZED PORCELAIN

WOOD LOOK

SIZES

| | | | Thickness | Sq. Ft./ Carton | Pieces/ Carton |
|--|----------------------|--|-----------|--------------------|-------------------|
|  | 6 x 36 Floor Tile | (5-7/8" x 35-7/16") (15.00 cm x 90.00 cm) | 5/16" | 13.05 | 9 |
|  | 6 x 24 Floor Tile | (6-1/16" x 23-7/8") (15.40 cm x 60.60 cm) | 5/16" | 14.53 | 15 |

APPLICATIONS


| | Target DCOF wet | Suitable |
|--|--------------------|----------|
| Dry & Level – Interior Floor | N/A | ✓ |
| Wet & Level – Interior Floor | ≥ 0.42 | ✓ |
| Shower Floors (Residential or Light Commercial) | ≥ 0.42 | |
| Exterior Floor Applications (including pool decking & other wet areas with minimal footwear) | ≥ 0.60 | |
| Ramps & Inclines | ≥ 0.65 | |
| Walls/Backsplashes | N/A | ✓ |
| Countertops | N/A | ✓ |
| Pool Linings | N/A | |

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

| Grout Joint Recommendation | Shade Variation |
|---|---|
| 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) |  High (V3) |

PERFORMANCE CHARACTERISTICS

| | ASTM# | Result |
|---------------------|-------|-----------|
| Water Absorption | C373 | < 0.5% |
| Breaking Strength | C648 | > 275 lbs |
| Scratch Hardness | MOHS | 8.0 |
| Chemical Resistance | C650 | Resistant |

For additional information on test results, visit us at: daltille.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

| | | |
|-------------------------|---|------------------------------------|
| 1 Residential Bathrooms | ③ | All Residential / Light Commercial |
| 2 All Residential Areas | 4 | All Residential / Commercial |

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltille.com/Factors.

Special consideration must be given when installing tiles greater than 15 inches. Please refer to daltille.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit daltille.com.



PRE-CONSUMER
RECYCLED MATERIALS



MADE IN THE U.S.A.



REVEAL IMAGING®

All or select items within this series meet the requirements for these qualifications. For more information, visit daltille.com.