

DA 6996 W Pearl

Wall ventilation hood with dimmable ambient lighting for a unique lighting mood in your kitchen.



- Design highlight 35 1/2 (900)Inch wide bowed glass canopy
- Unique convenience Con@ctivity 2.0
- Energy-efficient and uniform lighting
 LED light strip
- Energy-efficient and quiet

EAN: 4002515780381 / material number: 10418850	
Construction type	
Wall ventilation hood	•
Design	
Color	Brilliant white
Edge extraction	•
Operating modes	
Recirculated mode	Convertible
Control panel	
Electronic controls	•
Light-touch controls	•
Power levels (number excl. Intensive)	3
Intensive setting	•
Programmable 'Intensive' switch-off	•
Delayed shutdown for 5 or 15 minutes	•
Programmable grease filter saturation indicator	•
Programmable charcoal filter saturation indicator	•
Cleaning convenience	
Easy-to-clean CleanCover hood liner	•
Networking of domestic appliances	
Automatic function Con@ctivity 2.0 (Zigbee)	•
Filter system	
Number of dishwasher-safe stainless steel grease filters	1
Lighting	
LED ClearView lighting	•
Light intensity in Lx	600
Color temperature in K	3,000
Light dimmer function	•
Ambient lighting white	<u> </u>
Blower	
Dual-action blower	
	•
	_ `
AC motor Air throughput with max. duct diameter in vented	- :
AC motor Air throughput with max. duct diameter in vented mode (not for external version)	Values upon request
AC motor	Values upon request
AC motor Air throughput with max. duct diameter in vented mode (not for external version) Air throughput Safety	Values upon request
AC motor Air throughput with max. duct diameter in vented mode (not for external version) Air throughput Safety Safety shut-off	Values upon request
AC motor Air throughput with max. duct diameter in vented mode (not for external version) Air throughput Safety Safety Safety shut-off Single-ply safety glass (ESG)	Values upon request
AC motor Air throughput with max. duct diameter in vented mode (not for external version) Air throughput Safety Safety Safety shut-off Single-ply safety glass (ESG) Technical data	Values upon request • • • 23 (583)
AC motor Air throughput with max. duct diameter in vented mode (not for external version) Air throughput Safety Safety Safety shut-off Single-ply safety glass (ESG) Technical data Overall hood height for vented and external in in.(mm)	•
AC motor Air throughput with max. duct diameter in vented mode (not for external version) Air throughput Safety Safety Safety shut-off Single-ply safety glass (ESG) Technical data Overall hood height for vented and external in in.(mm) Overall hood height for recirculation in in.(mm)	23 (583) 23 (583)
AC motor Air throughput with max. duct diameter in vented mode (not for external version) Air throughput Safety Safety Safety shut-off Single-ply safety glass (ESG) Technical data Overall hood height for vented and external in in.(mm) Overall hood height for recirculation in in.(mm) Canopy width in in.(mm)	23 (583) 23 (583) 23 (583) 35 1/2 (900)
AC motor Air throughput with max. duct diameter in vented mode (not for external version) Air throughput Safety Safety Safety shut-off Single-ply safety glass (ESG) Technical data Overall hood height for vented and external in in.(mm) Overall hood height for recirculation in in.(mm) Canopy width in in.(mm) Height of hood canopy in in.(mm)	23 (583) 23 (583) 35 1/2 (900) 23 (583)
AC motor Air throughput with max. duct diameter in vented mode (not for external version) Air throughput Safety Safety Safety shut-off Single-ply safety glass (ESG) Technical data Overall hood height for vented and external in in.(mm) Overall hood height for recirculation in in.(mm) Canopy width in in.(mm) Height of hood canopy in in.(mm)	• 23 (583) 23 (583) 35 1/2 (900) 23 (583) 21 1/4 (537)
AC motor Air throughput with max. duct diameter in vented mode (not for external version) Air throughput Safety Safety Safety shut-off Single-ply safety glass (ESG) Technical data Overall hood height for vented and external in in.(mm) Overall hood height for recirculation in in.(mm) Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Net weight in lbs. (kg)	• 23 (583) 23 (583) 35 1/2 (900) 23 (583) 21 1/4 (537) 62 (28.0)
AC motor Air throughput with max. duct diameter in vented mode (not for external version) Air throughput Safety Safety Safety shut-off Single-ply safety glass (ESG) Technical data Overall hood height for vented and external in in.(mm) Overall hood height for recirculation in in.(mm) Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m)	• 23 (583) 23 (583) 35 1/2 (900) 23 (583) 21 1/4 (537) 62 (28.0) 4 (1.5)
AC motor Air throughput with max. duct diameter in vented mode (not for external version) Air throughput Safety Safety Safety shut-off Single-ply safety glass (ESG) Technical data Overall hood height for vented and external in in.(mm) Overall hood height for recirculation in in.(mm) Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted	• 23 (583) 23 (583) 35 1/2 (900) 23 (583) 21 1/4 (537) 62 (28.0) 4 (1.5) •
AC motor Air throughput with max. duct diameter in vented mode (not for external version) Air throughput Safety Safety Safety shut-off Single-ply safety glass (ESG) Technical data Overall hood height for vented and external in in.(mm) Overall hood height for recirculation in in.(mm) Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Hard-wired	• 23 (583) 23 (583) 35 1/2 (900) 23 (583) 21 1/4 (537) 62 (28.0) 4 (1.5) • •
AC motor Air throughput with max. duct diameter in vented mode (not for external version) Air throughput Safety Safety Safety shut-off Single-ply safety glass (ESG) Technical data Overall hood height for vented and external in in.(mm) Overall hood height for recirculation in in.(mm) Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Hard-wired Total connected load in kW	• 23 (583) 23 (583) 35 1/2 (900) 23 (583) 21 1/4 (537) 62 (28.0) 4 (1.5) • 0.37
AC motor Air throughput with max. duct diameter in vented mode (not for external version) Air throughput Safety Safety Safety shut-off Single-ply safety glass (ESG) Technical data Overall hood height for vented and external in in.(mm) Overall hood height for recirculation in in.(mm) Canopy width in in.(mm) Height of hood canopy in in.(mm) Depth of hood canopy in in.(mm) Net weight in lbs. (kg) Length of electrical wire in ft (m) Standard plug fitted Hard-wired	• 23 (583) 23 (583) 35 1/2 (900) 23 (583) 21 1/4 (537) 62 (28.0) 4 (1.5) • •

More information at www.MieleUSA.com



DA 6996 W Pearl

Wall ventilation hood with dimmable ambient lighting for a unique lighting mood in your kitchen.




Installation notes	
Vent connection at top	•
Vent connection at top and rear	•
Diameter of vent connection in in.(mm)	6 (150)
Standard accessories	
Non-return flap	•
Reducer from 150 to 125 mm Ø	•
Wireless stick Con@ctivity 2.0 for KM	XKS 3000 Z



DA 6996 W Pearl

Wall ventilation hood with dimmable ambient lighting for a unique lighting mood in your kitchen.





DA 6998 W (Installation drawing) - USA

- 1) Cut-out for cooker hoods with hard-wired connection rather than a plug.
 2) Opening for ducting connection at the back. Vent Connection alternatively to the top.
 3) Ventilation grille positioned at the top for recirculation. A distance of at least 200 mm must be maintained between the top of the appliance and the ceiling or any furniture units installed above the appliance.