

KM 3465 G

Gas cooktop

with a dual wok burner for particularly wide ranging burner capacity.



- Simple controls -single-handed operation via rotary dial control
- Professional design 30 (762)Inch wide stainless steel trough
- Particularly versatile 4 burners incl. 1 dual wok

Type of heatingGasFuel typeGasConstruction type•Independent of oven•Design•Cast iron pot rest (matte black enameled)•Ring features•No. of rings4Ring•Positionfront leftTypeDual wok burnerMax. rating in W4500Positionrear leftTypeStandard burnerMax. rating in W2600Positionrear rightTypeStandard burnerMax. rating in W2600Positionrear rightTypeHigh-speed burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W2600Positionfront rightTypeStandard burnerMax. rating in W2600Operation via knobs•Electronic ignition with one-handed operation•Operation via knobs•Electronic ignition with one-handed operation•OuickStart•Dimensions in in. (width)30 (762)Dimensions in in. (width)30 (762)Dimensions in in. (width) with proud-mounted28 3/8 (720)Cutout dimensions in in. (depth) with proud-mounted28 3/8 (720)Weight in lbs. (kg)41 (19)Power cord length in m.21 1/2 (518)	EAN: 4002514141008 / material number: 06792700	
Fuel typeGasConstruction type•Independent of oven•Design•Cast iron pot rest (matte black enameled)•Ring features4No. of rings4Ringfront leftTypeDual wok burnerMax. rating in W4500Positionrear leftTypeStandard burnerMax. rating in W2600Positionrear rightTypeStandard burnerMax. rating in W2600Positionrear rightTypeHigh-speed burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W2600Positionrear rightTypeHigh-speed burnerMax. rating in W2600Positionfront rightTypeStandard burnerMax. rating in W2600Control panel•Operation via knobs•Electronic ignition with one-handed operation•QuickStart•SafetyGasStop & ReStartDimensions in in. (width)30 (762)Dimensions in in. (width) with proud-mounted installation21 3/8 (542)Cutout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in lbs. (kg)41 (19)	Type of heating	
Independent of oven•Design•Cast iron pot rest (matte black enameled)•Ring features4No. of rings4Ringfront leftTypeDual wok burnerMax. rating in W4500Positionrear leftTypeStandard burnerMax. rating in W2600Positionrear rightTypeStandard burnerMax. rating in W2600Positionrear rightTypeStandard burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W2600Operation via knobs•Electronic ignition with one-handed operation•QuickStart•SafetyImmensions (height) in in.(mm)GasStop & ReStart•Technical dataDimensions in in. (width)30 (762)Dimensions in in. (width) with proud-mounted installation28 3/8 (720)Cutout dimensions in in. (width) with proud-mounted installation20 1/2 (518)Weight in lbs. (kg)41 (19)		Gas
Independent of oven•Design•Cast iron pot rest (matte black enameled)•Ring features4No. of rings4Ringfront leftTypeDual wok burnerMax. rating in W4500Positionrear leftTypeStandard burnerMax. rating in W2600Positionrear rightTypeStandard burnerMax. rating in W2600Positionrear rightTypeStandard burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W2600Positionfront rightTypeStandard burnerMax. rating in W2600Operation via knobs•Electronic ignition with one-handed operation•QuickStart•SafetyImmensions (height) in in.(mm)GasStop & ReStart•Technical dataDimensions in in. (width)30 (762)Dimensions in in. (width) with proud-mounted21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted20 1/2 (518)Weight in lbs. (kg)41 (19)	Construction type	
Cast iron pot rest (matte black enameled)•Ring features4No. of rings4Ringfront leftPositionfront leftTypeDual wok burnerMax. rating in W4500Positionrear leftTypeStandard burnerMax. rating in W2600Positionrear rightTypeStandard burnerMax. rating in W2600Positionrear rightTypeHigh-speed burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W2600Positionfront rightTypeStandard burnerMax. rating in W2600Operation via knobs•Electronic ignition with one-handed operation•QuickStart•Safety•GasStop & ReStart•Dimensions in in. (width)30 (762)Dimensions (depth) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation20 1/2 (518)Weight in lbs. (kg)41 (19)		•
Ring features4No. of rings4Ringfront leftPositionfront leftTypeDual wok burnerMax. rating in W4500Positionrear leftTypeStandard burnerMax. rating in W2600Positionrear rightTypeStandard burnerMax. rating in W2600Positionrear rightTypeHigh-speed burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W2600Positionfront rightTypeStandard burnerMax. rating in W2600Positionfront rightTypeStandard burnerMax. rating in W2600Operation via knobs•Electronic ignition with one-handed operation•QuickStart•SafetyGasStop & ReStartDimensions in in. (width)30 (762)Dimensions (height) in in.(mm)5 (125)Dimensions (depth) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Cutout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in lbs. (kg)41 (19)	Design	
No. of rings4Ringfront leftPositionfront leftTypeDual wok burnerMax. rating in W4500Positionrear leftTypeStandard burnerMax. rating in W2600Positionrear rightTypeHigh-speed burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W2600Operation via knobs•Electronic ignition with one-handed operation•QuickStart•Safety•GasStop & ReStart•Dimensions in in. (width)30 (762)Dimensions (depth) in in.(mm)5 (125)Dimensions (depth) in in. (width) with proud-mounted installation28 3/8 (720)Cutout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in lbs. (kg)41 (19)	Cast iron pot rest (matte black enameled)	•
RingFont leftPositionfront leftTypeDual wok burnerMax. rating in W4500Positionrear leftTypeStandard burnerMax. rating in W2600Positionrear rightMax. rating in W2600Positionrear rightTypeHigh-speed burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W2600Positionfront rightTypeStandard burnerMax. rating in W2600Operation via knobs5Electronic ignition with one-handed operation•QuickStart•SafetysafetyDimensions in in. (width)30 (762)Dimensions (height) in in.(mm)5 (125)Dimensions (depth) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Weight in Ibs. (kg)41 (19)	Ring features	
Positionfront leftTypeDual wok burnerMax. rating in W4500Positionrear leftTypeStandard burnerMax. rating in W2600Positionrear rightTypeHigh-speed burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W2600Positionfront rightTypeStandard burnerMax. rating in W2600Operation via knobs•Electronic ignition with one-handed operation•QuickStart•SafetyGasStop & ReStart•Technical dataDimensions in in. (width)30 (762)Dimensions (depth) in in.(mm)5 (125)Dimensions (depth) in in. (width) with proud-mounted installation28 3/8 (720)Weight in lbs. (kg)41 (19)	No. of rings	4
TypeDual wok burnerMax. rating in W4500Positionrear leftTypeStandard burnerMax. rating in W2600Positionrear rightTypeHigh-speed burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W2600Positionfront rightTypeStandard burnerMax. rating in W2600Operation via knobs•Electronic ignition with one-handed operation•QuickStart•Safety•GasStop & ReStart•Technical data•Dimensions in in. (width)30 (762)Dimensions (depth) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Weight in lbs. (kg)41 (19)	Ring	
Max. rating in W4500Positionrear leftTypeStandard burnerMax. rating in W2600Positionrear rightTypeHigh-speed burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W2600Control panel0Operation via knobs•Electronic ignition with one-handed operation•QuickStart•Safety30 (762)Dimensions in in. (width)30 (762)Dimensions (depth) in in.(mm)5 (125)Dimensions (depth) in in. (width) with proud-mounted installation28 3/8 (720)Cutout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in Ibs. (kg)41 (19)	Position	front left
Positionrear leftTypeStandard burnerMax. rating in W2600Positionrear rightTypeHigh-speed burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W2600Positionfront rightTypeStandard burnerMax. rating in W2600Control panel0Operation via knobs•Electronic ignition with one-handed operation•QuickStart•Safety•GasStop & ReStart•Dimensions in in. (width)30 (762)Dimensions (height) in in.(mm)5 (125)Dimensions (depth) in in. (width) with proud-mounted installation28 3/8 (720)Cutout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in Ibs. (kg)41 (19)	Туре	Dual wok burner
TypeStandard burnerMax. rating in W2600Positionrear rightTypeHigh-speed burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W2600Positionfront rightTypeStandard burnerMax. rating in W2600Control panel2600Operation via knobs•Electronic ignition with one-handed operation•QuickStart•Safety•GasStop & ReStart•Dimensions in in. (width)30 (762)Dimensions (height) in in.(mm)5 (125)Dimensions (height) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Cutout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in Ibs. (kg)41 (19)	Max. rating in W	4500
Max. rating in W2600Positionrear rightTypeHigh-speed burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W2600Control panel2600Operation via knobs•Electronic ignition with one-handed operation•QuickStart•Safety•Dimensions in in. (width)30 (762)Dimensions (height) in in.(mm)5 (125)Dimensions (depth) in in. (width) with proud-mounted installation28 3/8 (720)Cutout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in Ibs. (kg)41 (19)	Position	rear left
Positionrear rightTypeHigh-speed burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W2600Control panelOperation via knobs•Electronic ignition with one-handed operation•QuickStart•SafetyGasStop & ReStart•Dimensions in in. (width)30 (762)Dimensions (depth) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Weight in Ibs. (kg)41 (19)	Туре	Standard burner
TypeHigh-speed burnerMax. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W2600Control panelOperation via knobs•Electronic ignition with one-handed operation•QuickStart•SafetyGasStop & ReStart•Dimensions in in. (width)30 (762)Dimensions (height) in in.(mm)5 (125)Dimensions (depth) in in. (width) with proud-mounted installation28 3/8 (720)Weight in Ibs. (kg)41 (19)	Max. rating in W	2600
Max. rating in W3500Positionfront rightTypeStandard burnerMax. rating in W2600Control panel2600Operation via knobs•Electronic ignition with one-handed operation•QuickStart•Safety•GasStop & ReStart•Technical data30 (762)Dimensions in in. (width)5 (125)Dimensions (height) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Weight in Ibs. (kg)41 (19)	Position	rear right
Positionfront rightTypeStandard burnerMax. rating in W2600Control panel2600Operation via knobs•Electronic ignition with one-handed operation•QuickStart•Safety•GasStop & ReStart•Technical data30 (762)Dimensions in in. (width)5 (125)Dimensions (height) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Outout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in Ibs. (kg)41 (19)	Туре	High-speed burner
TypeStandard burnerMax. rating in W2600Control panel2600Operation via knobs•Electronic ignition with one-handed operation•QuickStart•Safety•GasStop & ReStart•Technical data30 (762)Dimensions in in. (width)5 (125)Dimensions (height) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Outout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in Ibs. (kg)41 (19)	Max. rating in W	3500
Max. rating in W2600Control panel2600Operation via knobs•Electronic ignition with one-handed operation•QuickStart•Safety•GasStop & ReStart•Technical data•Dimensions in in. (width)30 (762)Dimensions (height) in in.(mm)5 (125)Dimensions (height) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Outout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in Ibs. (kg)41 (19)	Position	front right
Control panelOperation via knobs•Electronic ignition with one-handed operation•QuickStart•Safety•GasStop & ReStart•Technical data•Dimensions in in. (width)30 (762)Dimensions (height) in in.(mm)5 (125)Dimensions (depth) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Cutout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in Ibs. (kg)41 (19)	Туре	Standard burner
Operation via knobs•Electronic ignition with one-handed operation•QuickStart•Safety•GasStop & ReStart•Technical data•Dimensions in in. (width)30 (762)Dimensions (height) in in.(mm)5 (125)Dimensions (height) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Cutout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in Ibs. (kg)41 (19)	Max. rating in W	2600
Electronic ignition with one-handed operationQuickStartSafetyGasStop & ReStartTechnical dataDimensions in in. (width)30 (762)Dimensions (height) in in.(mm)5 (125)Dimensions (depth) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installationQuitout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in Ibs. (kg)	Control panel	
QuickStart•Safety•GasStop & ReStart•Technical data•Dimensions in in. (width)30 (762)Dimensions (height) in in.(mm)5 (125)Dimensions (depth) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Cutout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in Ibs. (kg)41 (19)	Operation via knobs	•
Safety•GasStop & ReStart•Technical data30 (762)Dimensions in in. (width)30 (762)Dimensions (height) in in.(mm)5 (125)Dimensions (depth) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Cutout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in Ibs. (kg)41 (19)	Electronic ignition with one-handed operation	•
GasStop & ReStart•Technical data30 (762)Dimensions in in. (width)5 (125)Dimensions (height) in in.(mm)5 (125)Dimensions (depth) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Cutout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in Ibs. (kg)41 (19)	QuickStart	•
Technical data30 (762)Dimensions in in. (width)5 (125)Dimensions (height) in in.(mm)5 (125)Dimensions (depth) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Cutout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in lbs. (kg)41 (19)	Safety	
Dimensions in in. (width)30 (762)Dimensions (height) in in.(mm)5 (125)Dimensions (depth) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Cutout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in Ibs. (kg)41 (19)	GasStop & ReStart	•
Dimensions (height) in in.(mm)5 (125)Dimensions (depth) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Cutout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in lbs. (kg)41 (19)		
Dimensions (depth) in in.(mm)21 3/8 (542)Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Cutout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in lbs. (kg)41 (19)	Dimensions in in. (width)	30 (762)
Cutout dimensions in in. (width) with proud-mounted installation28 3/8 (720)Cutout dimensions in in. (depth) with proud-mounted installation20 1/2 (518)Weight in lbs. (kg)41 (19)	Dimensions (height) in in.(mm)	5 (125)
installation 28 3/8 (720) Cutout dimensions in in. (depth) with proud-mounted installation 20 1/2 (518) Weight in lbs. (kg) 41 (19)		21 3/8 (542)
Installation 20 1/2 (518) Cutout dimensions in in. (depth) with proud-mounted 20 1/2 (518) Weight in lbs. (kg) 41 (19)		28 3/8 (720)
Weight in Ibs. (kg) 41 (19)	Cutout dimensions in in. (depth) with proud-mounted	
	Power cord length in m	3 (1.2)

More information at www.MieleUSA.com




KM 3465 G

Gas cooktop

with a dual wok burner for particularly wide ranging burner capacity.





KM 3464/KM3565 (USA) (Installation drawing)

- Front
 Installation heigth
 Gas connection
 Electrical connection