



TandemLED wireless controller

## TANDEMLED WIRELESS CONTROLLER

PART NUMBER	DESCRIPTION / OUTPUT	DIMENSIONS
T-T-1Z-WC-RF-Color	TandemLED™ wireless controller. Control 1 zone of lights, tune the color temperature of the lights, dim lights and turn off / on. Use with WAV Smart Receiver (T-TWAV-WR-120) or WAV Smart Receiver / Power Supply (T-WAV-60W-PSR). Available in Almond (AL), Black (BK), Brown (BR), Grey (GR), or White (WT).	2-5/8" x 1-5/16" x 3/8"

**Blue indicates customer choice. Color indicates Finish Color.**  
*T-T-1Z-WC-RF-GR (Example part number for TandemLED Wireless Controller in Grey)*

## FEATURES

- Wireless RF Controller to tune multi-white light from Warm White to Daylight White and all white temperatures in between
- Designed with backplate to fit into a standard decora style wall face plate
- Magnetic backing for easy removal from backplate
- 3-year limited warranty
- Designed for indoor application
- Use with WAV Smart Receiver to turn lights on / off / dim / or tune the white color temperature

## COLOR OPTIONS



## COMPATIBLE RECEIVERS

PART NUMBER	DESCRIPTION	DIMENSIONS
T-TWAV-WR-120	WAV 120 watt smart LED Receiver. Use with a Wireless Controller	4-1/4" x 2-1/4" x 3/8"
T-WAV-60W-PSR	60 watt AC/DC 2 prong plug-in, 12 volt DC 5 AMP with built in smart LED receiver	7-1/4" x 2-7/8" x 1-5/8"