
## **DUO CCT MINI WALL WASH 12V**


5121-27/30



## LANDSCAPE LIGHTING









Select Warm White (2700K) or Pure White light (3000K)

Continuously adjust brightness

#### **PRODUCT DESCRIPTION**

Landscape Wall Wash luminaire

#### **FEATURES**

- A uniform wide distribution wall wash from a small form factor
- Integral brightness control select color temperature option
- IP66 rated, Protected against high-pressure water jets
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Mounting stake, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- · Not suitable to use with external dimmers

### **SPECIFICATIONS**

**Input:** 9 - 15VAC (Transformer is required)

**Power:** 1W to 8W / 2VA - 12VA **Brightness:** 80 lm to 420 lm

Beam Angle: Asymmetrical (70° by 95°)

**CRI:** 85

Rated Life: 60,000 hours

#### ORDERING NUMBER

	Color Temp	Finish	
5121 Mini Wall wash 12V	<b>27/30</b> or	700K BK BZ BBR	Black on Aluminum Bronze on Aluminum Bronze on Brass

5121-

Example: 5121-27/30BZ

# **DUO CCT MINI WALL WASH 12V**

5121-27/30



Accessories					
Additional Stake	9000-ST9-BZ	9000-ST9-BZ			Durable PVC stake
Surface Mount Flange/Stake	5000-SCP-BZ 5000-SCP-BBR 5000-SCP-BK	5000-SCP-BBR		n	Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box
Guardian Mount	9000-SP9-BZ	9000-SP9-BZ			Heavy duty stainless steel spike to position fixture Formed from a single piece of metal
Gutter Mount Bracket	5000-GM-BZ 5000-GM-BK	Stainlass Staal			Stainless Steel universal mounting bracket for gutter mounting fixture
Tree Mount Junction Box	5000-TCP-BZ 5000-TCP-BK		Bronze on Aluminum Black on Aluminum		Bronze on Aluminum box with Stainless steel mounting screws. Two ½" NPT threaded holes
Optics	LENS-2X3-AMB LENS-2X3-GRN LENS-2X3-RED	Amber Green Red	LENS-2X3-BLU LENS-2X3-FR LENS-2X3-SPR	Blue Frosted Spread	Enhances saturation of florals and foliage
Extension Rods	5000-X04-BZ 5000-X04-BK 5000-X08-BZ 5000-X08-BK 5000-X12-BZ 5000-X12-BK	4 in 4 in 8 in 8 in 12 in 12 in	5000-X18-BZ 5000-X18-BK 5000-X24-BZ 5000-X24-BK	18 in 18 in 24 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler	5000-LCO-BZ		Bronze		

### Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

**9075-TRN-SS** *75W Max* 

**9150-TRN-SS** *150W Max* 

**9300-TRN-SS** *300W Max* 

**9600-TRN-SS** 600W Max

