


# IRIX – model: DR-356

## Crystal Collection: Beauty Spots™

# WAC LIGHTING

## Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

Beauty Spots™ series are low voltage surface mount fixtures designed for use in drywall ceilings, grid ceilings, walls, or displays. Clear shades fit over the lamp and are retained by a spring band.

### FEATURES

- Sold as a complete unit - housing and trim
- Use 12V/24V remote electronic or magnetic transformer (order separately) see next pages for complete transformer spec.
- Easily mounted on suspended or finished ceilings.
- Can be used individually as accent pieces or grouped together.
- LED and Xenon versions are dimmable with ELV dimmers
- 5 year WAC Lighting product warranty

### SPECIFICATIONS

**Construction:** Canopy faceplate is plated chrome. Wiring compartment is steel, painted black.

**Light Source:** LED 4.3W or Xenon Bi-Pin 20W with canopy.

**Mounting:** No screws, nails or hardware required. Flat "wing" springs expand against the cut out hole to hold fixture against the surface. 2 3/8" cut out hole.


**Mounting:** Integral wiring compartment with standard size knock out hole on top. When using a class II power supply, side hole may be used for wire entry

**Dimming:** ELV Dimming: 100%-10%

**Standards:** UL & cUL Listed.

### Integral LED

\* Dimming is not recommended




**DR-356LED-CL/CH** Irix

Color Temp	Lumens	Voltage	Wattage	Rated Life	Finish	Cutout
3000K	150	24V	4.5 W	50,000 hours	Clear / Chrome	2 3/8"

		Input	Output	Min Load	Dimension (L x W x H)	Max Fixture Run	Max Run Length
Remote Transformer for Integral LED	<b>EN-2460-RB2</b>	120V	24V, 60W (class 2)	1W	6 1/2" x 1 5/8" x 1 1/4"	12 per transformer	30'
	<b>EN-24100-RB2</b>	120V	24V, 96W (class 2)	1W	6 1/2" x 1 5/8" x 1 1/4"	21 per transformer	40'

### 12V Xenon Bi-Pin

\* Dimmable with compatible dimmer match to power supply



**DR-365-CL/CH** Irix

Color Temp	Lumens	Voltage	Wattage	Rated Life	Finish	Cutout
3000K	200	12V, 24V	20 W	10,000 hours	Clear/ Chrome	2 3/8"

		Input	Output	Min Load	Dimension (L x W x H)	Max Fixture Run	Max Run Length
Remote Transformer for Xenon Bi-pin	<b>EN-1260-RB2</b>	120V	12V, 60W (class 2)	1W	6 5/8" x 1 5/8" x 1 1/8"	3	25'
	<b>EN-12100-RB-AR</b>	120V	12V, 100W	1W	6 1/4" x 3" x 1 5/8"	5	30'
	<b>EN-12150-RB-AR</b>	120V	12V, 150W	1W	6 1/4" x 3" x 1 5/8"	7	35'

**WAC Lighting**  
www.waclighting.com  
Phone (800) 526.2588 • Fax (800) 526.2585

**Headquarters/Eastern Distribution Center**  
44 Harbor Park Drive • Port Washington, NY 11050  
Phone (516) 515.5000 • Fax (516) 515.5050

**Western Distribution Center**  
1750 Archibald Avenue • Ontario, CA 91760  
Phone (800) 526.2588 • Fax (800) 526.2585