Fixture Type:

Catalog Number:

Project:

Location:

Model & Size Color Temp & CRI Finish Watt LED Lumens Delivered Lumens PD-70913 13" 3000K 90 BK Black BN 11W 1099 745

Example: PD-70913-BN

For custom requests please contact customs@waclighting.com

DESCRIPTION

Symmetrical, cylindrical and aerodynamic. Brilliance alone or as a collection.

FEATURES

Flare

- 360 degree illumination
- Thin powered cables provide an ultra-clean look
- Driver concealed within the canopy
- 5 year warranty


SPECIFICATIONS

Color Temp:	3000K	
Input:	120-277 VAC,50/60Hz	
CRI:	90	
Dimming:	ELV: 100-10% , 0-10V: 100-10%,TRIAC: 100-10%	
Rated Life:	50000 Hours	
Standards:	ETL, cETL,Title 24 JA8-2019 Compliant	
	Damp Location Listed	
Construction:	Aluminum with PC diffuser	









waclighting.com | Phone (800) 526.2588 | Fax (800) 526.2585 | Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. April 2022

Fixture Type:

Catalog Number:

Project:

Location:

Pendant 3000K

Flare

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens
PD-70925 25"	3000K 90	BK Black BN Brushed Nickel	27W	2426	1700

Example: PD-70925-BN

For custom requests please contact customs@waclighting.com

DESCRIPTION

Symmetrical, cylindrical and aerodynamic. Brilliance alone or as a collection.

FEATURES

- 360 degree illumination
- Thin powered cables provide an ultra-clean look
- Driver concealed within the canopy
- 5 year warranty

SPECIFICATIONS


Color Temp:	3000K		
Input:	120-277 VAC,50/60Hz		
CRI:	90		
Dimming:	ELV: 100-10% , 0-10V: 100-10%,TRIAC: 100-10%		
Rated Life:	50000 Hours		
Standards:	ETL, cETL,Title 24 JA8-2019 Compliant		
	Damp Location Listed		
Construction:	Aluminum with PC diffuser		



FINISHES:







waclighting.com | Phone (800) 526.2588 | Fax (800) 526.2585 | Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. April 2022

Flare

Pendant 3000K

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size Color Temp & CRI Finish Watt **LED Lumens Delivered Lumens** PD-70937 37" 3000K 90 BK Black 37W 3801 2637 BN Brushed Nickel Example: PD-70937-BN For custom requests please contact customs@waclighting.com DESCRIPTION Symmetrical, cylindrical and aerodynamic. Brilliance alone or as a collection. FEATURES • 360 degree illumination • Thin powered cables provide an ultra-clean look · Driver concealed within the canopy • 5 year warranty SPECIFICATIONS 3000K Color Temp: 120-277 VAC,50/60Hz Input: 90 CRI: ELV: 100-10% , 0-10V: 100-10%, TRIAC: 100-10% Dimming: 50000 Hours Rated Life: ETL, cETL, Title 24 JA8-2019 Compliant Standards: Damp Location Listed Aluminum with PC diffuser **FINISHES: Construction:**







waclighting.com | Phone (800) 526.2588 | Fax (800) 526.2585 | Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. April 2022

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size Color Temp & CRI Finish Watt LED Lumens Delivered Lumens PD-70945 45" 3000K 90 BK Black BN 42W 4254 2853

Example: PD-70945-BN

For custom requests please contact customs@waclighting.com

DESCRIPTION

Symmetrical, cylindrical and aerodynamic. Brilliance alone or as a collection.

FEATURES

Flare

- 360 degree illumination
- Thin powered cables provide an ultra-clean look
- Driver concealed within the canopy
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K	
Input:	20-277 VAC,50/60Hz	
CRI:	0	
Dimming:	ELV: 100-10% , 0-10V: 100-10%,TRIAC: 100-10%	
Rated Life:	50000 Hours	
Standards:	ETL, cETL,Title 24 JA8-2019 Compliant	
	Damp Location Listed	
Construction:	Aluminum with PC diffuser	



FINISHES:



LINE DRAWING:

